Amendments to the Claims

This listing of the claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

- 1. (canceled)
- 2. (previously presented) The flat display as claimed in claim 16 wherein the first stand is hinged on the main body.
- 3-15 (canceled)
- 16. (currently amended) A flat display, comprising:
 - a main body;
 - a first stand connected to the main body; and
 - a second stand, detachably connected to the first stand;

wherein, the flat display stands on a surface by way of the main body and the first stand both contacting the surface when the second stand is detached from the first stand, and the flat display stands on the surface only by way of the second stand contacting the surface when the first and second stands are connected.

- 17. (previously presented) The flat display as claimed in claim 2, wherein when the flat display stands on the surface by way of the main body and the first stand, the main body and the first stand form a specific angle.
- 18. (previously presented) The flat display as claimed in claim 16, wherein the second stand comprises a flat bottom surface to stabilize the main body when the flat display stands on the surface only by way of the second stand.

Application No: 10/615,168 Page 4

19. (previously presented) The flat display as claimed in claim 16, wherein the first stand defines a hole, and the second stand comprises an engaging portion fit into the hole to allow connection between the first stand and the second stand.

- 20. (previously presented) The flat display as claimed in claim 19, wherein the second stand further comprises a first spring forcing the engaging portion to join the hole.
- 21. (previously presented) The flat display as claimed in claim 19, wherein the second stand further comprises a button forcing the engaging portion to separate from the hole, to detach the second stand from the first stand.
- 22. (currently amended) The flat display as claimed in claim 1619, wherein the second stand further comprises the second stand being hollow, comprising:

 a flat bottom surface at a first end of the second stand;

 an opening at a second end of the second stand for insertion of the first stand into the second stand, wherein the second end is opposite to the first end; and a rail inside the second stand for guiding insertion of the first stand into the second stand.
- 23. (currently amended) The flat display as claimed in claim 22, wherein the second stand further comprises a second spring disposed at a bottom of the rail, when pushing the first stand downward to the bottom of the rail, the second spring pushing against the first stand to push against the first stand when the first stand is inserted in the second stand.
- 24. (previously presented) The flat display as claimed in claim 23, wherein the second stand further comprises a button forcing the engaging portion to separate from the hole, the second spring forcing the first stand to separate from the second stand.
- 25. (previously presented) The flat display as claimed in claim 16, wherein when the flat display stands on the surface only by way of the second stand, the main body is suspended from the surface.

Application No: 10/615,168 Page 5

26. (currently amended) A flat display comprising:

- a main body;
- a first stand connected to the main body; and
- a second stand being hollow and detachably connected to the first stand;

wherein, the flat display stands on a surface by way of the main body and the first stand both contacting the surface when the second stand is detached from the first stand, and the flat display stands on the surface only by way of the second stand contacting the surface when the first stand is housed in the second stand.

- 27. (previously presented) The flat display as claimed in claim 26, wherein the first stand is hinged on the main body.
- 28. (previously presented) The flat display as claimed in claim 27, wherein when the flat display stands on the surface by way of the main body and the first stand, the main body and the first stand form a specific angle.
- 29. (currently amended) The flat display as claimed in claim 26, wherein the second stand comprises a flat bottom surface to stabilize the main body when the flat display stands on the surface only by way of the second stand. the second stand comprising:

 a flat bottom surface at a first end of the second stand;

 an opening at a second end of the second stand for insertion of the first stand into the second stand, wherein the second end is opposite to the first end; and
 a rail inside the second stand for guiding insertion of the first stand into the second stand.
- 30. (previously presented) The flat display as claimed in claim 26, wherein the first stand defines a hole, and the second stand comprises an engaging portion fit in the hole to allow connection between the first stand and the second stand.
- 31. (previously presented) The flat display as claimed in claim 30, wherein the second stand further comprises a first spring forcing the engaging portion to join in the hole.

Application No: 10/615,168 Page 6

32. (previously presented) The flat display as claimed in claim 30, wherein the second stand further comprises a button forcing the engaging portion to separate from the hole, to detach the second stand from the first stand.

- 33. (previously presented) The flat display as claimed in claim 30, wherein the second stand further comprises a rail inside for guiding insertion of the first stand into the Second stand.
- 34. (previously presented) The flat display as claimed in claim 33, wherein the second stand further comprises a second spring disposed at a bottom of the rail to push against the first stand when the first stand is inserted in the second stand.
- 35. (previously presented) The flat display as claimed in claim 26, wherein when the flat display stands on the surface only by way of the second stand, the main body is suspended from the surface.
- 36. (new) The flat display as claimed in claim 26 further comprising a carrying portion fixed to the main body and pivotally connected to the first stand, wherein the carrying portion comprises a handle for lifting the display.
- 37. (new) The flat display as claimed in claim 16 further comprising a carrying portion fixed to the main body and pivotally connected to the first stand, wherein the carrying portion comprises a handle for lift for lifting the display.